

Large versatile pear-shaped HMS carabiner with screw lock gate and removable captive bar designed especially as a fixed connector in anchor systems or lanyards. This carabiner keeps your gear well-arranged and minimizes the chance of cross loading.

DESCRIPTION

Anodized finishing increases corrosion resistance.

Angled snag free Keylock nose for smooth clipping and unclipping maneuvers.

Rough notches on the locking sleeve for easy manipulation even with gloves.

Each carabiner is individually tested for a strength of 10 kN.

Captive bar keeps the carabiner in its proper orientation. The bar is easily removable with an Allen key no. 3.



Large rope bearing area for better rope glide and reduced wear on the carabiner.

Gate opening and basket area are large enough to easily accommodate a big anchor point or more slings.

Hot-forged I-beam construction makes the carabiner extremely strong, stiff and light.

Excellent ergonomics provides perfect handling with the carabiner.

KEY FEATURES

- large opening (26 mm)
- excellent ergonomics
- high strength (30 kN)

STANDARDS

C € 1019

EN 12275, type H EN 362, class B

FEATURES









26 mm



85 g / 3 oz



unique number




warranty


MATERIALS

TECHNICAL DATA



95 % aluminium alloy **5**% stainless steel





production batch MMYY (month, year)

unique serial number XXXX



COMPARISON

HECTOR / screw - LARGO / screw

- strength encreased from 22 to 30 kN
- weight reduced from 100 to 83 g
- more rough notches on locking sleeve
- better ergonomics
- available also in black color and with captive bar



LARGO / screw

MAINTENANCE

Lifetime of the product is not strictly limited by the manufacturer. Depending on the condition of the product and its history it may be necessary to retire it immediately.

Mobile components may be lubricate the with a specific silicone based lubricant.

83 g







91 g





read instructions



89 g



WEIGHT

NOTES

85 g